

3M™ DBI-SALA® Sealed Blok™ Self-Retracting Lifelines

Stainless Steel Cable, 15 ft. and 30 ft. Lengths

**Our heaviest-duty
Class 1 SRL.**



Effective March 24, 2023, 3M™ DBI-SALA® Sealed Blok™ Stainless Steel Cable Self-Retracting Lifelines in 15 ft. and 30 ft. lengths in overhead, retrieval and retrieval with bracket models will meet the new ANSI/ASSP Z359.14-2021 standard with Class 1 certification, as well as the OSHA 1926.502 & OSHA 1910.140 regulations.

3M™ DBI-SALA® Sealed Blok Class 1 Stainless Steel Cable Self-Retracting Lifelines now have new part numbers and labels to reflect the updates. This will help you identify Sealed Blok™ products meeting the ANSI Z359.14-2021 standard moving forward.

Please note, Class 1 SRD classification is for use with anchorages AT or ABOVE the dorsal D-ring.

Existing Part Number	New Part Number	Description
3400827	3400131	3M™ DBI-SALA® Sealed-Blok™ Self-Retracting Lifeline 340013, Class 1, Stainless Steel Cable, 15 ft.
3400802	3400133	3M™ DBI-SALA® Sealed-Blok™ Self-Retracting Lifeline 3400133, Class 1, Stainless Steel Cable, 30 ft.
3400852	3400144	3M™ DBI-SALA® Sealed-Blok™ Self-Retracting Lifeline 3400144, Retrieval, Class 1, Stainless Steel Cable, 30 ft.
3400858	3400145	3M™ DBI-SALA® Sealed-Blok™ 3-Way Retrieval Self-Retracting Lifeline with Bracket 3400145, Class 1, Stainless Steel Cable, 30 ft.

Products manufactured to previous revisions of the ANSI Z359.14 standard may continue to be used as long as the product continues to meet the inspection requirements as defined by the manufacturer, conducted at the recommended intervals by a Competent Person.

For more information on ANSI/ASSP Z359.14-2021 product certifications and what the standard update means for you, contact your 3M Fall Protection Representative or visit [3M.com/ANSIupdate](https://www.3m.com/ANSIupdate).

3M™ DBI-SALA® Sealed Blok™ Self-Retracting Lifelines

Stainless Steel Cable, 15 ft. and 30 ft. Lengths

Below is a performance comparison for 3M™ DBI-SALA® Sealed Blok™ Self-Retracting Lifelines against the Industry Standard requirements:

	Previous Performance Claims		New Performance Claims		
	ANSI/ASSP Z359.14-2014, OSHA 1926.502, & OSHA 1910.140	OSHA 1926.502 & OSHA 1910.140	ANSI/ASSP Z359.14-2021	OSHA 1926.502 & OSHA 1910.140	
SRD Class	Class B		Class 1		
Weight Capacity	130 to 310 lb.	311 to 420 lb.	130 to 310 lb.	130 to 310 lb.	311 to 420 lb.
Maximum Arrest Force	900 lb.	1,800 lb.	1,350 lb.	1,350 lb.	1,800 lb.
Average Arrest Force	900 lb.	N/A	1,125 lb.	1,125 lb.	N/A
Arrest Distance	42 in.	42 in.	30 in.	30 in.	42 in.

	Industry Standard Requirements			
	ANSI/ASSP Z359.14-2014		OSHA 1926.502 & OSHA 1910.140	ANSI/ASSP Z359.14-2021
SRD Class	Class A	Class B		Class 1 and 2
Weight Capacity	130 to 310 lb.	130 to 310 lb.	N/A	130 to 310 lb.
Maximum Arrest Force	1,800 lb.	1,800 lb.	1,800 lb.	1,800 lb.
Average Arrest Force	1,350 lb.	900 lb.	N/A	1,350 lb.
Arrest Distance	24 in.	54 in.	42 in.	*42 in.



3M Fall Protection
3833 SALA Way
Red Wing, MN 55066 USA

Phone 800.328.6146
Email 3mfallprotection@mmm.com
Web 3M.com/FallProtection

3M, DBI-SALA and Sealed Blok are trademarks of 3M Company.
© 2023, 3M. All rights reserved.